

XP 909

MATTE BLACK/CHROMESILVER



GRAPHIC SIMULATION ONLY / REAL PICTURE SOON

MTB HARDTAIL / RACE

BENEFITS

- A new generation of triple-butted, cutting-edge aluminium frame, BOOST standard hubs, tapered headset, and completely inner routing
- Lightweight, remote lockout RockShox Judy Silver TK R BOOST fork with a travel of 100 mm
- 1x11 Shimano drivetrain with a large range of gears to suit various terrain patterns
- Schwalbe Racing Ralph tires for a safer and more comfortable ride in rough terrain
- Thru-axles improve the stiffness and stability in terrain rides or intensive braking

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	585	610	630	650
REACH (MM)	415	437	455	472
STACK HEIGHT (MM)	591	600	609	619
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	69	69	69	69
CHAINSTAY LENGTH (MM)	440	440	440	440
BB DROP (MM)	55	55	55	55
WHEELBASE (MM)	1105	1130	1151	1172
HANDLEBAR WIDTH (MM)	760/720	760/720	760/720	760/720
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	400	400	400	400

SPECIFICATION

FRAMESET

RAHMEN	Alu X6 Ultralite, Race Geometry, Conical Head Tube, BB92, Boost Thru axle 148x12mm, Inner cable routing
STEUERSATZ	Head set cover, ACROS AZX-212 R5,ZS44/28.6 ZS56/40
GABEL	RockShox Judy Silver TK R, Tapered, SoloAir, 15x110mm axle, 100mm travel
COLOUR	MATTE BLACK/CHROMESILVER
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

Schalthebel	SHIMANO DEORE SL-M5100-IR RapidFire Plus, 11-speed
SCHALTWERK	SHIMANO DEORE RD-M5100 Shadow Plus
KETTENRADGARNITUR	ONE1 TAM38-D34NC, 34T
CASSETE	SHIMANO CS-M5100-11, 11-51T
INNENLAGER	SHIMANO BB-MT500PA PressFit, shell 41x92mm
KETTE	KMC X11

COMPONENTS

LENKER	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
VORBAU	ONE1 TDS-D507 Alloy, 31.8mm, -7°
GRIFFE	ONE1 VLG-1661D2N, Lock-On
BREMSEN	SHIMANO BL-M4100/BR-MT410, hydraulic disc brake
SATTEL	Saddle
SATTELSTÜTZE	ONE1 Race Alloy, SP 218, 27.2mm

WHEELS

NABE HR	SHIMANO FH-MT400-B, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
FELGEN	Stars J25DH, 32H
REIFEN	Schwalbe Rapid Rob KevlarGuard, 29x2.10"
Speichen	Sapim Leader, Stainless Black